

Hydraulic Vari-Width Bale Handler

The Cashels **Hydraulic Vari-Width Bale Handler** has been designed to handle, transport and stack both 4ft (1220mm) and 5ft (1525mm) round, wrapped bales. This is a heavy duty bale handler suitable for industrial loaders.



Designed to be used on either front or rear 3-point linkage of tractors, as well as front loaders; from skid steer to tractor to telehandlers. With this in mind, the unit comes fitted with a combination 3-point linkage/Euro linkage as standard to cater for the majority of users. Other linkages available on enquiry.





Kev Features:

- Heavy duty construction throughout with high quality paint finish.
- 43" (1100mm) CAT 2 stone fork tines with rotating tubes to prevent damage to bale film when handling.
- Hydraulic hoses & fittings supplied as standard or to suit customer requirements.
- Rotating tubes are easily removed, allowing the unit to be used for spiking during feeding season.
- Hot-dip galvanised roller tubes.

See video on www.cashels.net

Length	Width	Height	Linkage	Load Capacity	Net Weight	Max Opening	Max Closed	Tractor HP
1450mm <i>(57")</i>	1405mm <i>(55″)</i>	885mm <i>(35")</i>	EURO	1 Bale 1000kg <i>(2200lbs)</i>	220kg (484lbs)	1655mm <i>(65″)</i>	1060mm <i>(42")</i>	60+