

PULVERIZER FIXED / 4-SERIES



| GLOBRAM PULVERIZERS fixed, 4-SERIES | | RM 412X | RM 416X | RM 426X | RM 436X | RM 443X | RM 450X |
|---------------------------------------------|-------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
| Excavator weight min | tons | 6 | 10 | 16 | 20 | 28 | 33 |
| Excavator weight max | tons | 18 | 21 | 30 | 45 | 55 | 65 |
| Excavator weight optimum min | tons | 7 | 12 | 18 | 24 | 30 | 36 |
| Excavator weight optimum max | tons | 18 | 21 | 30 | 45 | 55 | 65 |
| Attachment operating weight (incl. bracket) | kg | 750 | 1300 | 1800 | 2800 | 3450 | 4400 |
| Max. opening | mm | 650 | 810 | 900 | 1000 | 1190 | 1290 |
| Height | mm | 1700 | 1900 | 2100 | 2440 | 2590 | 2850 |
| Width | mm | 980 | 1190 | 1470 | 1540 | 1630 | 1800 |
| Jaw width | mm | 345 | 400 | 450 | 520 | 560 | 610 |
| Oil delivery min | l/min | 80 | 120 | 140 | 150 | 180 | 180 |
| Oil delivery max | l/min | 200 | 200 | 220 | 250 | 260 | 300 |
| Max. working pressure | bar | 350 | 400 | 400 | 400 | 400 | 400 |
| Max. clamping force at tip | ton | 50 | 65 | 80 | 105 | 120 | 135 |
| Max. clamping force at shears | ton | 160 | 210 | 265 | 355 | 380 | 410 |
| Shear length | mm | 100 | 180 | 240 | 240 | 240 | 360 |
| Max. cutting diameter | mm | 40 | 40 | 45 | 50 | 50 | 50 |
| Min. closure time | sec | 2 | 2 | 3 | 2 | 2,5 | 2,5 |
| Min. opening time | sec | 1 | 1 | 1,5 | 2 | 2,5 | 2,5 |
| Hydraulic connections open/close | inch | 3 / 4" | 3 / 4" | 3 / 4" | 1" | 1" | 1" |
| Cradle plate compatibility | | RM 90 | RM 120 - 130 | RM 140 - 150 | RM 160 | RM 180 - 195 | RM 180 - 195 |
| Cradle plate dimensions | mm | 540 x 420 12 x Ø 22 | 640 x 480 12 x Ø 22 | 730 x 550 12 x Ø 27 | 750 x 750 12 x Ø 30 | 740 x 740 12 x Ø 39 | 740 x 740 12 x Ø 39 |