

**PULVERIZER WITH ROTATION / 5-SERIES**


GLOBRAM PULVERIZERS rotation, 5-SERIES		RM 518X	RM 523X	RM 528X	RM 536X	RM 544X	RM 554X
Excavator weight min	tons	10	14	18	25	30	38
Excavator weight max	tons	25	30	36	45	55	65
Excavator weight optimum min	tons	12	16	20,5	27	32	42
Excavator weight optimum max	tons	25	30	36	45	55	65
Attachment operating weight (incl. bracket)	kg	1150	1700	2300	2950	3600	4500
Max. opening	mm	660	820	900	960	1050	1150
Height	mm	1860	2280	2510	2645	2800	3150
Width	mm	1000	1300	1450	1470	1480	1650
Jaw width	mm	340	410	450	490	520	570
Oil delivery min	l/min	80	120	140	150	150	180
Oil delivery max	l/min	200	200	220	250	250	300
Max. working pressure	bar	350	400	400	400	400	400
Max. clamping force at tip	ton	50	65	80	95	105	120
Max. clamping force at shears	ton	170	210	265	325	355	380
Shear length	mm	100	180	240	240	240	240
Max. cutting diameter	mm	40	40	45	50	50	50
Min. closure time	sec	2	2	3	2	2	2,5
Min. opening time	sec	1	1	1,5	2	2	2,5
Hydraulic connections open/close	inch	3 / 4"	3 / 4"	3 / 4"	1"	1"	1"
Max. rotation flow	l/min	20	25	25	30	30	30
Max. rotation pressure	bars	110	110	110	110	110	110
Hydraulic connections for rotation	inch	3 / 8"	1 / 2"	1 / 2"	1 / 2"	1 / 2"	1 / 2"
Cradle plate compatibility		RM 90	RM 120 - 130	RM 140 - 150	RM 160	RM 180 - 195	RM 180 - 195
Cradle plate dimensions	mm	540 x 420 12 x Ø 22	640 x 480 12 x Ø 22	730 x 550 12 x Ø 27	750 x 750 12 x Ø 30	740 x 740 12 x Ø 39	740 x 740 12 x Ø 39