









PCX 60A PLATE COMPACTOR





FEATURES & BENEFITS

- 11kN high performance Vibrator for maximum compaction and excellent travel speeds.
- Ergonomic operator handle for precise manouverability, includes Pull-Back bar.
- Thickener Plate in rear of Baseplate for increased durability.
- Specially engineered Fabricated Baseplate designed to eradicate 'Track' marks on asphalt.
- Collapsable handle for easy storage and transportation.
- 3 mount HAV system for reduced HAV levels and improved usage time.
- Optional 'Easy-Fit' 12-litre Water Tank & 'Easy-Clean' Spraybar system.
- Durable metallic Water Control Tap for high flow rate.
- Low HAV handles that still allow precision control.
- Optional Integrated 'Quick Engage' Wheel Kit.
- Handle Latch for increased stability whilst operating the Wheel Kit.



OPTIONAL 'EASY-FIT' 12LTR
WATER TANK



OPTIONAL INTEGRATED 'OUICK ENGAGE' WHEEL KIT



HANDLE LATCH FOR INCREASED STABILITY WHILST OPERATING THE WHEEL KIT

Detachable Water Kit

Integrated Wheel Kit

Paving Pad

TECHNICAL SPECIFICATIONS

Model	PCX 60A		
Part No.	PCU02		
Plate Size (W x L)	(mm)	350 x 400	
Width	(mm)	350	
Length - Operation	(mm)	1010	
Height - Operation	(mm)	1010	
Length - Storage	(mm)	660	
Height - Storage	(mm)	550	
Engine Power	(Hp/kW)	4/3	
*Weight	(kg)	68.5	
Static Pressure	(kg/m^2)	565	
Centrifugal Force	(kN)	11	Options
Frequency	(Hz)	101	OPP/87/DIO
Max. Travel Speed	(m/min)	25	OPP/86/DIO
Max. Gradient	(°)	20	OPP/65/DIO
**Vibration level	(m/sec^2)	4.9	

(dB(A))

105

* Weight does not include Water Kit or Wheel Kit.

** Vibration levels tested to BS5349 using EN 500-4



Noise Level

ALTRAD BELLE
Sheen, Nr. Buxton, Derbyshire, SK17 OEU, GB
Tel. +44 (0)1298 84606 - Fax +44 (0)1298 84722 - Email: sales@altrad-belle.com
www.Altrad-Belle.com
www.ALTRAD-Belle247.com

