

HALFZWAARGEWICHT

Specificaties	RM 120		RM 130		RM 135		RM 140		RM 145	
Bedrijfsklaar gewicht (incl. ophanging en beitel)	1245	kg	1535	kg	1700	kg	1850	kg	2230	kg
	2740	lbs	3380	lbs	3750	lbs	4080	lbs	4920	lbs
Gewicht hamer (zonder ophanging en beitel)	950	kg	1200	kg	1300	kg	1450	kg	1750	kg
	2090	lbs	2650	lbs	2870	lbs	3200	lbs	3860	lbs
Diameter beitel	119	mm	130	mm	135	mm	140	mm	144	mm
	4,69	in.	5,12	in.	5,31	in.	5,51	in.	5,67	in.
Volumestroom (bij werkdruk)	115 - 150	l/min	125 - 160	l/min	130 - 155	l/min	150 - 180	l/min	165 - 200	l/min
	30 - 40	gpm	33 - 42	gpm	34 - 41	gpm	40 - 48	gpm	44 - 53	gpm
Werkdruk (aan de hamer)	120 - 138	bar	120 - 138	bar	120 - 145	bar	130 - 150	bar	130 - 158	bar
	1740 - 2000	psi	1740 - 2000	psi	1740 - 2100	psi	1890 - 2180	psi	1890 - 2290	psi
Retourdruk (max.)	8	bar	7	bar	7	bar	8	bar	7	bar
	116	psi	102	psi	102	psi	116	psi	102	psi
Slagenergie	2500	J	3200	J	3700	J	4000	J	5000	J
	2500	J	3200	J	3700	J	4000	J	5000	J
Aantal slagen per minuut	490 - 925	1/min	425 - 875	1/min	400 - 860	1/min	400 - 840	1/min	400 - 745	1/min
	490 - 925	1/min	425 - 875	1/min	400 - 860	1/min	400 - 840	1/min	400 - 745	1/min
Aanbevolen machinegewicht	15 - 24	t	17 - 28	t	18 - 28	t	20 - 32	t	22 - 37	t
	17 - 26	tons	19 - 31	tons	20 - 31	tons	22 - 35	tons	24 - 41	tons
Totale hoogte (zonder ophanging; incl. beitel)	2140	mm	2265	mm	2310	mm	2490	mm	2595	mm
	84,3	in.	89,2	in.	90,9	in.	98,0	in.	102,2	in.