



STANDARD EQUIPMENT

- Integrated control panel
- Phase inverter
- Pump with peripheral impeller
- Flowmeter for pump protection
- Pressure gauge for outlet pressure reading
- Stainless steel crown with nozzles
- Water drain system
- Low speed trailer with drowbar, two wheels and jockey wheel
- Forklift pockets
- Two height adjustable rear stabilizers and two front stabilizers
- Manual rotation and tilting system

OPTIONS

- Automatic rotation
- Electric tilting
- Dedicated colour (RAL) (for spray cannon only)
- Ball or eyelet hitch
- Water supply pump
- Remote control
- Available without trailer

		DF 4500
TECHNICAL DATA		
Electrical engine power (kW)		4
Smaller generator required		Three-phase - 7.9 kW
Max. horizontal range (m)	Without wind	20 - 30
Max. vertical range (m)	Without wind	12
Max. covered area (m <sup>2</sup> )	With rotation on	2590
Electrical connection	Inlet plug	Three-phase socket - 32 A
Water connection	Available plugs	UNI 45 / STORZ / CAMLOCK
Min./Max. inlet pressure (bar)		1 / 4
Water consumption (L/min)		22 L/min
Water inlet filter (µm)		170
Working angle (°)		330
Tilting angle (°)		-20 / +40
Dimensions (mm)	Length x Width x Height	1780 x 1165 x 1800
Weight (kg)		290