

# DF 7500 MPT

EN\_CTS\_DF-7500-MPT\_1910\_r1.0



Version on optional low speed trailer

## STANDARD EQUIPMENT

- 2000 litres water tank, 100% stainless steel
- 17 kW integrated generating set
- Complete with 4 wheels, tow bar and forklift pockets
- Automatic rotation system
- Integrated control panel
- Two pumps with peripheral impellers
- Flowmeter for pump protection
- Pressure gauge for outlet pressure reading
- Stainless steel crown with nozzles
- Water drain system
- Four height adjustable stabilizers
- Electric tilting
- Remote control to switch on/off the fan, the pump and the electrical rotation

## OPTIONS

- Low speed trailer (without brakes)
- Dosing pump for chemical additives
- Arctic kit
- 110V kit for the generating set
- Remote control for the generating set
- Double nozzles holder crown
- Dedicated colour (RAL) (for spray cannon only)
- Rigid adjustable drawbar with 76mm eyelet hitch (for low speed trailer only)

## DF 7500 MPT

### TECHNICAL DATA

Electrical engine power (kW)		7.5
Integrated generating set		17 kW - 230 V - Diesel engine 1500 RPM
Max. horizontal range (m)	Without wind	30 - 40
Max. vertical range (m)	Without wind	17
Max. covered area (m <sup>2</sup> )	With rotation on	4600
Running time (min)	1 pump / 2 pumps	85 min (7 bar) / 60 min (12 bar)
Fuel tank capacity (L)		85
Water tank capacity (L)		2000
Water consumption (L/min)	1 pump / 2 pumps	23 L/min (7 bar) / 32 L/min (12 bar)
Water inlet filter (µm)		180
Working angle (°)		335
Tilting angle (°)		+0 / +40
Dimensions on trailer (mm)	Length x Width x Height	4450 x 2240 x 2640
Dry weight on trailer (kg)		2450